



CFJ240S

RCCB 2P 40A 300mA AC Class 60Hz

Technical attributes	CFJ240S
Altitude	2000 m
Bottom removability for modular devices	No
Construction size (DIN 43880)	1
Degree of pollution according to IEC 60664 / IEC 60947-2	2
Residual current trip mode	Undelayed
Short-time delayed tripping	No
Frequency	60 Hz
Height of installed product	83 mm
Idm: Breaking and opening capacity	1.5 Ka
Idn	300 mA
Rated residual operating current	
IN	40 A
Rated current	
Inc	6 kA
Rated conditional short-circuit current Inc according to EN 61008-1	
IP	IP20
Protection index IP	
Largeur_produit_inst	35 mm
Width of installed product	
Fixing mode	Din-Rail
	2
Number of modules	
Number of poles	2
	2000
Electric endurance in number of cycles	
	4000
Number of mechanical operations	
	left
Neutral position	
degree 360° product mounting position	Yes
Depth of installed product	70 mm
	25mm ²
Connection cross-sect. rigid cable	



Connection cross-sect. flexible conductor	16mm ²
Compatible with DIN rail mounting	Yes
Standard text	IEC 61008-1
Top removability for modular devices	No
Type of Bottom Connection for modular devices	Biconnect
Type of bottom rail clip for modular devices	metallic
Type of connection	with screw
Residual current type	AC
U_e	127 V
Rated operational voltage U_e	
U_i	500 V
Rated insulation voltage	
U_{imp}	4000 V
Rated impulse withstand voltage	